



ITALIAN QUALITY ITALIAN QUALITY ITALIAN QUALITY ITALIAN QUALITY

PEG No	SECTION REF	INTERNAL		SECTION		QUANTITY
		mm	ins	mm	ins	
1	E	3,0	0,118	2,0	0,078	18
2	E	4,0	0,157	2,0	0,078	18
3	E	5,0	0,197	2,0	0,078	17
4	E	6,0	0,236	2,0	0,078	17
5	E	7,0	0,276	2,0	0,078	17
6	E	8,0	0,315	2,0	0,078	17
7	E	10,0	0,394	2,0	0,078	17
8	E	12,0	0,472	2,0	0,078	17
9	F	10,0	0,394	2,5	0,098	13
10	F	12,0	0,472	2,5	0,098	13
11	F	14,0	0,551	2,5	0,098	13
12	F	15,0	0,59	2,5	0,098	13
13	F	17,0	0,669	2,5	0,098	13
14	F	19,0	0,748	2,5	0,098	13
15	G	18,0	0,709	3,0	0,118	11
16	G	20,0	0,787	3,0	0,118	13
17	G	22,0	0,866	3,0	0,118	13
18	G	24,0	0,945	3,0	0,118	13
19	G	25,0	0,984	3,0	0,118	13
20	G	28,0	1,102	3,0	0,118	13
21	G	30,0	1,181	3,0	0,118	13
22	H	30,0	1,181	3,5	0,138	11
23	H	32,0	1,260	3,5	0,138	11
24	H	33,0	1,300	3,5	0,138	11
25	H	35,0	1,378	3,5	0,138	11
26	G	34,0	1,338	3,0	0,118	13
27	G	36,0	1,417	3,0	0,118	13
28	G	38,0	1,496	3,0	0,118	13
29	G	40,0	1,575	3,0	0,118	13
30	G	42,0	1,654	3,0	0,118	13



**METRIC " 0" RING KIT**

**MATERIAL:** NITRIL RUBBER, 70 SH.A  
**TEMP:** RANGE -40 C TO + 120° C / -40 F TO 248° F  
**COMPATIBILITY:** MINERAL BASED OILS AND GREASES.  
 THESE PARTS ARE SUITABLE FOR DYNAMIC AND STATIC APPLICATIONS.

**MATERIAL:** NITRIL GUMMI 70 SH.A  
**TEMPERATUR:** - BEREICH -40° C + 120° C  
**EINSETZBAR:** FUR MINERALOLE UND SCHMIERFETTE.  
 DIESE TEILE GROSSEN GEEIGNET FUR DYNAMISCHE UND STATISCHE ANWENDUNGEN



ALL DIMENSIONS NOMINAL  
 ALLE GROSSEN NOMINAL

